



Innovation and Experience at Work

TriboGel 831

TriboGel 831 is an automotive and industrial synthetic grease intended for wide temperature and demanding applications. The features of the grease include:

- Excellent load carrying capacity under boundary conditions
- Excellent corrosion protection
- Dampening
- Broad operating temperature range (-40 to 150°C)

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
Туре			Synthetic Hydrocarbon
Temperature Service Range (°C)			-40 to 150
GREASE CHARACTERISTICS			TYPICAL VALUE *
Thickener			Calcium Complex
Color			Blue
Appearance			Smooth
NLGI Grade			1
Penetration (ASTM D217 / DIN 51804-T1)	Unworked		300 min.
	Worked	60X	320-360
Oil Separation (ASTM D6184)	24h at 100°C		5% max.
Evaporation (CTM-1)	24h at 100°C		1% max.

*The values stated in this Product Data Sheet are Typical Values and *must not* be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.