

EvoLube R601D

This evolutionary, polyurea-thickened grease contains PTFE and has outstanding long-life properties. Polyurea thickeners act to inhibit oxidation, thereby adding to the long-life effectiveness of this grease. This product contains a very light viscosity white mineral oil which gives it excellent low temperature properties at -45°F. It can also operate at temperatures up to +400°F. It is a shear stable, multi-purpose, water resistant grease and is compatible with most plastics and seals. There are no heavy metals in this product making it environmentally friendly.

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
Type			Mineral Oil
Temperature Service Range (°C)			-40 to 200
GREASE CHARACTERISTICS			TYPICAL VALUE *
Thickener			Polyurea
Color			Blue
Appearance			Smooth
NLGI Grade			2
Penetration (ASTM D217 / DIN 51804-T1)	Worked	60X	265-295
		100,000X	300
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)			260 min.
Oil Separation (ASTM D1742)			24h at 25°C and 1.72 kPa
Evaporation (CTM-1)			24h at 100°C
Water Washout (ASTM D1264 / DIN 51807-T2)			3.92%
Copper Corrosion (ASTM D130 / DIN 51811)			24h at 100°C
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _r		0.47mm
	Dynamic Coefficient of Friction (steel on steel)		0.050
Specific Gravity (CTM-2)			25°C
Low Temperature Torque (ASTM D1478)	-40°C	Start	3,153 gm-cm (0.309 N-m)
		Run 10 min	1,788 gm-cm (0.175 N-m)
		Run 60 min	455 gm-cm (0.044 N-m)

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.