



Innovation and Experience at Work

IsoTech B4008

This water-insoluble polyalkylene glycol oil is formulated to provide excellent lubrication, thermal and oxidative stability, and extended service life, while eliminating many of the problems associated with petroleum gear lubricants.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Туре		Polyalkylene Glycol
Temperature Service Range (°C)		-20 to 150
Viscosity (ASTM D445)	at 40°C	321-354 cSt
Color (ASTM D5386)		14
Specific Gravity (CTM-2)	20°C	1.0
pH (ASTM E70)	16.7% in isopropanol/water, 10:6)	7.2
Water Content (ASTM E203)		0.10%

*The values stated in this Product Data Sheet are Typical Values and *must not* be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.