



A QUAKER HOUGHTON COMPANY

Innovation and Experience at Work

# Product Data Sheet

## TriboGel 1876

TriboGel 1876 is a viscous damping fluid for use in motion control applications.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Polybutene
Temperature Service Range (°C)		5 to 95
GREASE CHARACTERISTICS		TYPICAL VALUE *
Color		Colorless
Specific Gravity (CTM-2)	25°C	0.90
Viscosity (ASTM D445)	40°C	58,000 cSt

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

### Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [eclusa\\_customer@quakerhoughton.com](mailto:eclusa_customer@quakerhoughton.com) • [www.eclube.com](http://www.eclube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.