



A QUAKER HOUGHTON COMPANY

Innovation and Experience at Work

# Product Data Sheet

## UltraSil 1025

UltraSil 1025 is a silicone compound designed to seal out moisture and prevent corrosion of electrical contacts. It is fortified with zinc oxide for good thermal conduction and reduced oil separation and has excellent dielectric strength.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Silicone
Temperature Service Range (°C)		-50 to 200
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Silica
Color		White
Appearance		Smooth
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	185-215
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.
Oil Separation (ASTM D6184)	24h at 100°C	0%
Evaporation (CTM-1)	24h at 100°C	0.20%
Specific Gravity (CTM-2)	25°C	1.52

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

### Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [eclusa\\_customer@quakerhoughton.com](mailto:eclusa_customer@quakerhoughton.com) • [www.eclube.com](http://www.eclube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.