



*Innovation and Experience at Work*

# CHRISTO-LUBE® 5120

Formerly called Absolube 5120

CHRISTO-LUBE® 5120 is PFPE fluid cut with non-combustible fluorinated solvent. When this material is applied, the solvent evaporates and leaves behind a thin film of oil. This lubricant has excellent low temperature properties and is inert to oxygen and other aggressive chemicals. The PFPE fluid has extremely low surface tension and this gives CHRISTO-LUBE® 5120 the ability to work in applications where other lubricants fail due to lubricant starvation. The fully fluorinated chemistry is completely compatible with a vast majority of plastics and elastomers.

CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		PFPE
<b>Color</b>		Colorless
<b>Temperature Service Range (°C)</b>		-40 – 200
<b>Flash Point (°C) (ASTM D-92)</b>		None
<b>Four Ball Wear (ASTM D2266 / DIN 51350-T5)</b>	60min 1200rpm 40kg <sub>f</sub> 75°C	0.7mm

**Engineered Custom Lubricants**      ISO/TS16949:2009 • Registered QMS  
 3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.