



Innovation and Experience at Work

CHRISTO-LUBE® B4011

Formerly called AbsoLube B4011

CHRISTO-LUBE® B4011 is high technology perfluoropolyether fluid that possesses excellent thermal stability and resistance to chemicals and oxygen-rich environment. Its very low pour point and excellent oxidative stability allow it to function in a very broad temperature range. CHRISTO-LUBE® B4011 also possesses excellent radiation hardness and low evaporation loss that make it suitable for aerospace applications. Since it is non-reactive with metal, plastic, rubber, and other elastomers, it is useful in a wide variety of applications. It also has an extremely high viscosity index which means that its viscosity changes less than many other fluids as temperature changes. PFPE fluids have extremely low surface tension that allows them to work in situations where other lubricants fail due to lubricant starvation.

CHARACTERISTICS	TYPICAL VALUE *
Type	PFPE
Color	Colorless
Temperature Service Range (°C)	-60 – 300
Flash Point (°C) (ASTM D-92)	None
Specific Gravity at 25°C	1.83

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.