



*Innovation and Experience at Work*

## IsoTech B4008

This water-insoluble polyalkylene glycol oil is formulated to provide excellent lubrication, thermal and oxidative stability, and extended service life, while eliminating many of the problems associated with petroleum gear lubricants.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		Polyalkylene Glycol
<b>Temperature Service Range (°C)</b>		-20 to 150
<b>Viscosity (ASTM D445)</b>	at 40°C	321-354 cSt
<b>Color (ASTM D5386)</b>		14
<b>Specific Gravity (CTM-2)</b>	20°C	1.0
<b>pH (ASTM E70)</b>	16.7% in isopropanol/water, 10:6)	7.2
<b>Water Content (ASTM E203)</b>		0.10%

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.