



Innovation and Experience at Work

IsoTech B4009

IsoTech B4009 is a polyalkylene glycol fluid, which offers low coefficient of friction, and excellent elastomer compatibility. IsoTech B4009 is highly refined to eliminate inorganic impurities which minimizes sludge, varnish, and carbon deposited upon breakdown, or when used in high temperature applications.

CHARACTERISTICS		TYPICAL VALUE *
Туре		Polyalkylene Glycol
Color		Clear - Water White
Temperature Service Range (°C)		-40 to 130
Viscosity (ASTM D445)	at 40°C	54.4-58.3 cSt
Specific Gravity at 20°C		0.99
Refractive Index		1.4482

*The values stated in this Product Data Sheet are Typical Values and *must not* be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.