



Innovation and Experience at Work

IsoTech B4009

IsoTech B4009 is a polyalkylene glycol fluid, which offers low coefficient of friction, and excellent elastomer compatibility. IsoTech B4009 is highly refined to eliminate inorganic impurities which minimizes sludge, varnish, and carbon deposited upon breakdown, or when used in high temperature applications.

CHARACTERISTICS		TYPICAL VALUE *
Type		PAG
Color		Clear - Water White
Temperature Service Range (°C)		-40 to 130
Viscosity (ASTM D445)	at 40°C	54.4-58.3 cSt
Specific Gravity at 20°C		0.99
Refractive Index		1.4482

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.