



## CHRISTO-LUBE® MCG 148

CHRISTO-LUBE® MCG 148 is a fully fluorinated, medium viscosity PFPE grease thickened with PTFE and cut with a fluorinated solvent. This grease operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This medium consistency fluorinated lubricant is especially useful where non-reactivity with harsh chemicals, fuels and solvents is an important factor.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		PFPE
<b>Temperature Service Range (°C)</b>		-50 to 250
<b>Flash Point (°C) (ASTM D92)</b>		None
GREASE CHARACTERISTICS		
<b>Thickener</b>		PTFE
<b>Color</b>		White
<b>Appearance</b>		Smooth
<b>NLGI Grade</b>		2
<b>Penetration (ASTM D217 / DIN 51804-T1)</b>	Unworked	265-295
	Worked	60X 265-295
<b>Oil Separation (ASTM D6184)</b>	24h at 149°C	10% max.
<b>Evaporation (CTM-1)</b>	24h at 149°C	3% max.
<b>Water Washout (ASTM D1264 / DIN 51807-T2)</b>	60 min at 79°C	0.50%
<b>Four Ball Wear (ASTM D2266 / DIN 51350-T5)</b>	60 min 1200 RPM 75°C 40kg <sub>f</sub>	0.83mm
	Dynamic Coefficient of Friction (steel on steel)	0.093
<b>Specific Gravity (CTM-2)</b>	25°C	1.691