



Innovation and Experience at Work

TriboGel 1412

TriboGel 1412 is a polyurea and calcium sulfonate grease with PTFE and polymer additives. This grease provides good damping, good EP/antiwear capability, great fretting wear protection, and excellent water resistance. Ideal for loaded metal to metal applications and this grease is resistant to degradation from high temperature welding and washout during autophoretic coating processes.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Polyurea / Calcium Sulfonate
Color		Green
Appearance		Smooth
NLGI Grade		1.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	285-315
	Worked	60X 285-315
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		240 min.
Oil Separation (ASTM D6184)	24h at 100°C	3% max.
Evaporation (CTM-1)	24h at 100°C	1% max.
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _f	0.348mm
	Dynamic Coefficient of Friction (steel on steel)	0.06

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.