



Innovation and Experience at Work

TriboGel 752

TriboGel 752 is fully synthetic polyurea thickened grease with a polymer additive. This grease provides moderate dampening, good EP/antiwear capability, and excellent water resistance. Applications include small gears and automotive recliners. TriboGel 752 is also resistant to degradation from high temperature welding and washout during autophoretic coating processes.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 125
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Polyurea
Color		Off White
Appearance		Smooth
NLGI Grade		1.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	295
	Worked	291
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		>260
Oil Separation (ASTM D6184)	24h at 100°C	0.11%
Evaporation (CTM-1)	24h at 100°C	0.14%
Specific Gravity (CTM-2)	25°C	0.88
Apparent Viscosity (Brookfield Viscometer T-C spindle, 1 rpm)	-40°C	5,900,000 cP
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _r	0.59mm
Oxidation Stability (ASTM D942 / DIN 51808)	100h at 100°C	3.5 kPa

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@eclube.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.