



Innovation and Experience at Work

TriboGel 968VL

TriboGel 968VL is synthetic hydrocarbon polytetrafluoroethylene thickened light dampening grease. This grease is fortified with a corrosion inhibitor and an extreme pressure additive.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *	
Type		Synthetic Hydrocarbon	
Temperature Service Range (°C)		-45 – 120	
GREASE CHARACTERISTICS		TYPICAL VALUE *	
Thickener		PTFE	
Color		Off White	
Appearance		Smooth	
NLGI Grade		2	
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	265-295	
	Worked	60X 265-295	
Oil Separation (ASTM D6184)	24h at 100°C	2% max.	
Evaporation (CTM-1)	24h at 100°C	1% max.	
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _f	0.73mm	
Low Temperature Torque (ASTM D1478)	-40°C	Start	1,892 g-cm
		Run 60 min	780 g-cm

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.