



**Innovation and Experience at Work**

## TriboGel PA6110UV

TriboGel PA6110UV is synthetic PAO based grease with outstanding performance over high and low temperature extremes. It has excellent chemical stability and works well with most materials including plastics and elastomers. It resists oxidation and corrosion of metal surfaces. TriboGel PA6110UV is designed for noise dampening and motion control applications. It has an ultraviolet dye added to it to enhance detection of it in a thin film.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 125
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		0.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	344
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.
Oil Separation (ASTM D6184)	24h at 100°C	1.97%
Evaporation (CTM-1)	24h at 100°C	0.24%
Apparent Viscosity (Brookfield Viscometer T-C spindle, 1 rpm)	-40°C	5,900,000 cP

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.