



Innovation and Experience at Work

ViscoTech B6019

ViscoTech B6019 is a bentone-thickened grease formulated with virgin paraffinic base oils. It contains additives to improve extreme pressure and antiwear as well as corrosion and oxidation inhibitors.

GREASE CHARACTERISTICS			TYPICAL VALUE *
Temperature Service Range (°C)			-20 to 100
Thickener			Bentone
Color			Tan
Appearance			Smooth
NLGI Grade			0
Penetration (ASTM D217 / DIN 51804-T1)	Worked	60X	355 - 385
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)			>260
Oil Separation (ASTM D6184)	24h at 100°C		7.8%
Evaporation (CTM-1)	24 at 100°C		0.46%
Copper Corrosion (ASTM D130 / DIN 51811)	24h at 100°C		1b
Specific Gravity (CTM-2)	25°C		0.8

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@eclube.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.