

CHRISTO-LUBE® 1204

Formerly called Absolube 1204

CHRISTO-LUBE® 1204 is synthetic grease made from polyfluoropolyether (PFPE) fluid thickened with polytetrafluoroethylene (PTFE) polymer. This grease has excellent low temperature properties and is inert to oxygen and other aggressive chemicals. The PFPE fluid has extremely low surface tension and this gives CHRISTO-LUBE® 1204 the ability to work in applications where other lubricants fail due to lubricant starvation. The fully fluorinated chemistry is completely compatible with a vast majority of plastics and elastomers

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Temperature Service Range (°C)		-40 to 200
Flash Point (°C) (ASTM D92)		None
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	265-295
	Worked	60X 265-295
Oil Separation (ASTM D6184)	24h at 100°C	5% max.
Evaporation (CTM-1)	24h at 100°C	2% max.
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		200 min.
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kg _f	0.86mm
	Dynamic Coefficient of Friction (steel on steel)	0.113

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@eclube.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.