

CHRISTO-LUBE® MCG 195

CHRISTO-LUBE® MCG 195 is a fully fluorinated grease thickened with PTFE which operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This soft consistency fluorinated lubricant is especially useful in lubricating under-hood automotive components where high temperature stability and non-reactivity with chemicals and fuels are important factors.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Temperature Service Range (°C)		-25 to 260
Flash Point (°C) (ASTM D92)		None
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		0.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	330-360
	Worked	60X 330-360
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		200 min.
Oil Separation (ASTM D6184)	24h at 149°C	10% max.
Evaporation (CTM-1)	24 at 149°C	3% max.

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.