



Innovation and Experience at Work

CHRISTO-LUBE® MCG 1030

CHRISTO-LUBE® MCG 1030 is a fully fluorinated oil which operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This high viscosity, low vapor pressure PFPE oil has excellent thin-film strength and was formulated specifically for reducing friction and wear in precision high vacuum applications.

CHARACTERISTICS	TYPICAL VALUE *
Type	PFPE
Color	Colorless
Temperature Service Range (°C)	-23 to 260
Flash Point (°C) (ASTM D-92)	None
Specific Gravity at 25°C	1.92

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@eclube.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.