



A QUAKER CHEMICAL COMPANY

Innovation and Experience at Work

Lubricants for Doors & Sunroofs

**Long life. Wide-temperature.
Smooth, quiet performance.**

Quality benchmarks that give our customers a competitive edge.



Tracks, Rollers & Cables

A very efficient grease allows for smaller, lighter window lift motors – and longer life.

TriboGel 3506	PAO/ CaSul	Low bleed, wide temperature, corrosion resistant grease with good wear protection for metal rails.
UltraSil 712	Silicone/Lithium PTFE	Low temperature, noise reducing, dust resistant grease with excellent wetting characteristics for long life.
UltraSil 1104	Silicone/PTFE	Outstanding adhesion, water and dust resistant. Extremely smooth operation.

Door Latches & Hinges

A water-resistant grease that protects against corrosion and wear, adds years to latch and hinge life.

RheoGel B6005	PAO/CaSul	For latches, strong wear resistance, corrosion protection and responsive low temperature performance.
RheoGel TEK676	PAO/CaSul	For hinges, low oil separation and fortified for extreme pressure, wear resistance and corrosion protection.
Friction Fighter 820	PTFE/MoS ₂ Coating	For latches and hinges, a greaseless, low friction, dry coating for a no-mess lubricant solution.



Door Lock Actuators

All moving parts in an actuator benefit from very low oil bleed and friction reducing additives.

EvoLube TEK670	PAO/Urea	Low temperature, multi-purpose grease for gears, cams and pivot points.
UltraSil 1104	Silicone/PTFE	Extremely low friction, low bleed grease for plastic gears and screws that allows for great back drive.
RheoGel 1216	PAO/Lithium Polymer	Low bleed, wear resistant, low temperature grease with additives that reduce noise.

Side View Mirrors

Small motors need low-bleed, low-torque greases that can also minimize motor noise.

RheoGel 916A	PAO/Lithium PTFE	Low temperature, water resistant, highly efficient grease for small motors.
RheoGel 305HF	PAO/Lithium PTFE	Wide temperature, low bleed, good stay in place grease for metal and plastic parts.
UltraSil 712	Silicone/Lithium PTFE	Extremely efficient grease across wide temperatures. Formulated to reduce motor noise.

Seals

Lubricating weather sealing with a thin, paint-safe and elastomer-safe coating that eliminates itching.

AbsoLube B4011	PFPE	Transparent oil, compatible with all door seal elastomers.
AbsoLube 5120	PFPE	AbsoLube B4011 mixed in a solvent for easy, even, thin film depositing.
IsoTech B4009	PAG	EPDM compatible, low odor and low cost oil for door and sunroof seals.



A QUAKER CHEMICAL COMPANY

ECLI Products, LLC 3851-3847 Exchange Ave. Aurora, IL 60504 USA Tel. +1-630-449-5000 Fax +1-630-585-0050

ECL Engineered Custom Lubricants GmbH Stormsweg 5A, 22085 Hamburg, Germany Tel. +49 40 386660-80 Fax +49 40 386660-81

www.ecllube.com ISO/TS16949:2009 Registered QMS

ECLI Products, LLC, does business as Engineered Custom Lubricants (ECL).